现货库存 技术资料 百科信息 热点资讯 精彩尽在鼎好!

TOSHIBA PHOTOCOUPLER GaAs IRED & PHOTO-TRIAC

TLP160G

TRIAC DRIVE

PROGRAMMABLE CONTROLLERS

AC-OUTPUT MODULE

SOLID STATE RELAY

Unit in mm



TOSHIBA 11-4C3

Weight : 0.09g

The TOSHIBA MINI FLAT COUPLER TLP160G is a small outline coupler, suitable for surface mount assembly.
The TLP160G consists of a photo triac, optically coupled to a gallium arsenide infrared emitting diode.

- Peak Off-State Voltage : 400V (MIN.)
- Trigger LED Current : 10mA (MAX.)
- On-State Current : 70mA (MAX.)
- Isolation Voltage : 2500Vrms (MIN.)
- UL Recognized : UL1577, File No. E67349

TRIGGER LED CURRENT

CLASSIFICATION*	TRIGGER LED CURRENT (mA) V_T=3V, Ta=25°C		MARKING OF CLASSIFICATION
	MIN.	MAX.	
(IFT5)	—	5	T5
(IFT7)	—	7	T5, T7
Standard	—	10	T5, T7, Blank

*Ex. (IFT5) ; TLP160G (IFT5)
(Note) Application type name for certification test, please use standard product type name, i.e.
TLP160G (IFT5) : TLP160G

PIN CONFIGURATIONS



1. ANODE
3. CATHODE
4. TERMINAL 1
6. TERMINAL 2

961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta = 25°C)

	CHARACTERISTIC		SYMBOL	RATING	UNIT
LED	Forward Current		I_F	50	mA
	Forward Current Derating (Ta ≥ 53°C)		ΔI_F / °C	−0.7	mA / °C
	Peak Forward Current (100μs pulse, 100pps)		I_{FP}	1	A
	Reverse Voltage		V_R	5	V
	Junction Temperature		T_j	125	°C
DETECTOR	Off-State Output Terminal Voltage		V_{DRM}	400	V
	On-State RMS Current	Ta = 25°C	$I_{T(RMS)}$	70	mA
		Ta = 70°C		40	
	On-State Current Derating (Ta ≥ 25°C)		ΔI_T / °C	−0.67	mA / °C
	Peak On-State Current (100μs pulse, 120pps)		I_{TP}	2	A
	Peak Nonrepetitive Surge Current (PW = 10ms, DC = 10%)		I_{TSM}	1.2	A
	Junction Temperature		T_j	115	°C
Storage Temperature Range			T_{stg}	−55~125	°C
Operating Temperature Range			T_{opr}	−40~100	°C
Lead Soldering Temperature (10s)			T_{sol}	260	°C
Isolation Voltage (AC, 1 min., R.H. ≤ 60%) (Note)			BV_S	2500	Vrms

(Note) Device considered a two terminal device : Pins 1 and 3 shorted together and pins 4 and 6 shorted together.

RECOMMENDED OPERATING CONDITIONS

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage	V_{AC}	—	—	120	Vac
Forward Current	I_F	15	20	25	mA
Peak On-State Current	I_{TP}	—	—	1	A
Operating Temperature	T_{opr}	−25	—	85	°C

INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta = 25°C)

	CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
LED	Forward Voltage	V_F	I_F = 10mA	1.0	1.15	1.3	V
	Reverse Current	I_R	V_R = 5V	—	—	10	μA
	Capacitance	C_T	V = 0, f = 1MHz	—	30	—	pF
DETECTOR	Peak Off-State Current	I_{DRM}	V_{DRM} = 400V	—	10	1000	nA
	Peak On-State Voltage	V_{TM}	I_{TM} = 70mA	—	1.7	2.8	V
	Holding Current	I_H	—	—	0.6	—	mA
	Critical Rate of Rise of Off-State Voltage	dv / dt	V_{in} = 120Vrms, Ta = 85°C (Fig.1)	200	500	—	V / μs
	Critical Rate of Rise of Commutating Voltage	dv / dt (c)	I_T = 15mA, V_{in} = 30Vrms (Fig.1)	—	0.2	—	V / μs

COUPLED ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Trigger LED Current	I_{FT}	V_T = 3V	—	5	10	mA
Capacitance Input to Output	C_S	V_S = 0, f = 1MHz	—	0.8	—	pF
Isolation Resistance	R_S	V_S = 500V, R.H. ≦ 60%	1×10^{12}	10^{14}	—	Ω
Isolation Voltage	BV_S	AC, 1 minute	2500	—	—	Vrms
		AC, 1 second, in oil	—	5000	—	
		DC, 1 minute, in oil	—	5000	—	Vdc
Turn-on Time	t_{ON}	V_D = 6→4V, R_L = 100Ω, I_F = Rated $I_{FT}\times1.5$	—	30	100	μs

Fig.1 dv / dt TEST CIRCUIT



I_F – Ta



$I_{T(RMS)}$ – Ta



I_{FP} – D_R



I_F – V_F



$\Delta V_F / \Delta Ta$ – I_F



I_{FP} – V_{FP}



NORMALIZED I_{FT} – Ta



NORMALIZED I_H – Ta



NORMALIZED I_{DRM} – Ta



NORMALIZED V_{DRM} – Ta



NORMALIZED LED CURRENT – LED CURRENT PULSE WIDTH